


WOODS & FINISHES:

Natural Maple


Standard



Natural Clear – M-NA

Maple Finishes


The following stains are available, add 10% to list




Castle Oak – M-CO




Honey Oak – M-HO




English Oak – M-EN




Victorian Cherry – M-VI



Richmond Cherry – M-RC



Mahogany – M-MA




Java – M-JA



Wenge – M-WE

Natural Red Oak


Standard




Natural Clear – O-NA

Red Oak Finishes


The following stains are available, add 10% to list




Castle Oak – O-CO




Honey Oak – O-HO




English Oak – O-EN




Victorian Cherry – O-VI




Richmond Cherry – O-RC



Mahogany – O-MA




Java – O-JA



Wenge – O-WE

Natural Cherry


Add 20% to list




Natural Clear – C-NA

Cherry Finishes

The following stains are available, add 30% to list




Honey Oak – C-HO



Richmond Cherry – C-RC

Natural Walnut


Add 20% to list



Natural Clear – W-NA

Walnut Finishes

The following stain is available, add 30% to list



Java – W-JA

WILSONART® LAMINATES:

Solid, Abstract and Wood Grain Options




Frosty White
1573-60



Black
1595-60



Island
D498-60



Blue Agave
4919-60



Mambo
7948-60



Grey Elm
8201-38




Natural Almond
D30-60




Indigo
D379-60




Hunter Green
D79-60




Eggplant
4913-60




Cocobala
7942-38



Phantom Cocoa
8213-38



Beige
1530-60



Sunshine
D499-60



Ocean
D502-60



Spiced Zephyr
4859-60



Walnut Heights
7965-38



Studio Teak
7960-38



Fashion Grey
D381-60



Orange Grove
D501-60



Lapis Blue
D417-60



Morro Zephyr
4846-60



Wild Cherry
7054-60



Skyline Walnut
7964-38



Dove Grey
D92-60



Hollyberry
D307-60



Maroochy Brush
4745-60



Fusion Maple
7909-60



Phantom Pearl
8211-38



Phantom Charcoal
8214-38




Slate Grey
D91-60



Port
D14-60



Woolamai Brush
4746-60



Bannister Oak
7806-60




White Driftwood
8200-38



Asian Night
7949-38

METAL PAINT:

Thermal Paint Colours




White
PS-111-W374




Antique White
W11



Beige
H23



Desert
H432



Red
R66




Ruby
R7




Blue
B11



Navy
B17




Zinc
A67



Hydro Green
G96




Green
G58




Grey
A16




Charcoal
A230




Black
N49




Pebble
M237



Black Sandtex
N31




Sparkle Silver
S11



Champagne
S14

EDGE BAND COLOURS:


PVC edge band colour options




Hardrock Maple
AC-WM791



Natural Oak
AC-FWG9877



Chocolate Tick
AC-FWG7424




White
AC-SW811



Antique White
AC-W11



Beige
AC-H23




Desert
AC-H432




Red
AC-R66




Ruby
AC-R7



Blue
AC-B11



Navy
AC-B17




Zinc
AC-A67




Hydro Green
AC-G96



Green
AC-G58




Grey
AC-A16



Charcoal
AC-A230



Black
AC-N49



Pebble
AC-M237

HARDWOODS: All hardwood materials used in the manufacturing of Palmieri products shall be Northern grown hardwoods. Hardwoods will be air and kiln dried to a moisture content of 5-7%. All hardwoods shall be of grade "A" material, free of material stains, imperfections, conformity of grain, texture and color. Hardwood species shall be Northern grown Red Oak, Clear White Northern Maple and Birch. American Cherry and Honduras Mahogany and Walnut are available. Please inquire for pricing.

VENEER: Exposed face veneers shall be not less than 1/28" thick plain sliced veneers. Veneers are to be selected for conformity of grain direction and color. Veneers are to be stitched tightly in a book match, slip match or plain sliced configuration. Unexposed veneers are to be of hardwood but not selected for color, or grain quality. Veneers are not to be lap joined or reveal any tape or glue lines.

PARTICLE BOARD CORE: The particleboard shall be formed of wood chips, bonded with a water resistance adhesive. The particleboard material is to be of a high density 45 lbs/cu. ft. having a minimum average modulus of rupture of 2400 psi and a minimum average modulus of elasticity of 4,000,000 psi.

VENEER CORE: Veneer core is to be constructed with odd numbers of plies. Each ply is to be laminated in pairs and cross banded in opposite directions with grain direction at a 90 degree angle to the grain of the center core. All plies are to be free from knots, wrinkles, laps or other natural or manufacturing defects.

LUMBER CORE: Lumber core is to be of the highest quality grade. Grade "A" select stock. Lumber core shall be constructed of solid random width strips not less than 2" wide nor more than 3 1/2" wide by 1" thick. Wood strips will be free from knots or other defects. All strips will be tightly joined using water resistance adhesives.

HIGH PRESSURE LAMINATE: Work surface laminate shall be .050" thick and used with balancing backer sheet of no less than .028" thick. Laminate shall conform to standards set by the American Standards Institute/National Electrical Manufacturers Association (ANSI/NEMA) for thickness, performance and appearance. Printed colours, abstract patterns and wood grains are reproduced from representative segments of large sheets and may differ slightly from the actual product.

FINISHING PROCEDURES: All materials shall be inspected and treated with a final sanding and polishing operation before any staining and final finishing can be performed. All machine and mill marks are to be removed. Once the polishing and sanding has been performed, the furniture will then undergo the following stain and finishing procedures:

- Step 1 A base stain will be uniformly applied, wiped and then allowed to dry under factory controlled conditions.
- Step 2 A uniform coat of sealer will be applied and allowed to dry.
- Step 3 Sealer will be lightly sanded using 240 grit silicon paper.
- Step 4 A catalytic lacquer of 34-45 degree sheen is evenly applied and allowed to dry under factory controlled conditions.

METAL FINISHING PROCEDURES: All metal components are thoroughly cleaned and coated electrostatically with an epoxy powder coat paint finish. The metal components are then oven baked and cured for a lasting finish.

EDGE BANDS: All edge bands are manufactured in PVC, semi-rigid (Flex) and ABS. Standard edging size are normally 1.25" wide x 3 mm thick. These are made of the highest grade polymers and its materials are extensively tested prior to production using special test procedures and industry specification and quality standards.